

TRI固定接頭, 依據DIN 32676和ISO 2853

應用

- 食品工業, 製藥工業
- 真空輸送設備, 真空料斗, 吸入式輸送機, 配料系統
- 造粒機/壓片機

特性

- 符合 RoHS 規定

- REACH according to --> 技術 / 技術資訊 / REACH

溫度範圍

- -40°C 至 90°C

結構

配置: 不銹鋼 1.4404 (標刻) = AISI 316L; 相配的附

件, 包含: 密封圈 (白色矽膠, FDA), 接頭 (不銹鋼 1.4404, 標刻), 管束 (不銹鋼)

其他產品資訊

- 可提供其它長度及直徑產品
- 防氣體及液體滲漏的預先安裝版

額定尺寸	額定寬度管	法蘭盤外徑	重量	適合的軟管內徑 d2	訂購代碼
mm		法蘭	千克/個		
三片式管束接頭 DIN 32676; 不銹鋼 (INOX)1.4404 (標刻) = AISI 316L; 請分別選擇軟管和裝配					
25	-	50,5	0,090	ø 25	245-0025-2914
32	-	50,5	0,090	ø 32	245-0032-2914
40	-	50,5	0,080	ø 40	245-0040-2914
50	-	64,0	0,160	ø 50	245-0050-2914
65	-	91,0	0,180	ø 65	245-0065-2914
80	-	106,0	0,380	ø 80	245-0080-2914
100	-	119,0	0,420	ø 100	245-0100-2914
三片式管束接頭 ISO 2852; 不銹鋼 (INOX)1.4404 (標刻) = AISI 316L; 請分別選擇軟管和裝配					
-	1"	50,5	0,090	ø 25	245-0025-2923
-	1 1/2"	50,5	0,110	ø 40	245-0040-2923
-	2"	64,0	0,160	ø 50	245-0050-2923
-	2 1/2"	77,5	0,170	ø 65	245-0065-2923
-	3"	91,0	0,350	ø 75	245-0075-2923
-	4"	119,0	0,420	ø 100	245-0100-2923
相配的附件; 密封圈 DIN32676; 矽膠, 白色					
25	-	50,5	-	ø 25	245-0025-8912
32	-	50,5	-	ø 32	245-0032-8912
40	-	50,5	-	ø 40	245-0040-8912
50	-	64,0	-	ø 50	245-0050-8912
65	-	91,0	-	ø 65	245-0065-8912
80	-	106,0	-	ø 80	245-0080-8912
100	-	119,0	-	ø 100	245-0100-8912
相配的附件; 密封圈 ISO 2852; 矽膠, 白色					
-	1"	50,5	-	ø 25	245-0025-8916
-	1 1/2"	50,5	-	ø 40	245-0040-8916
-	2"	64,0	-	ø 50	245-0050-8916
-	2 1/2"	77,5	-	ø 65	245-0065-8916
-	3"	91,0	-	ø 75	245-0075-8916
-	4"	119,0	-	ø 100	245-0100-8916
相配的附件; 管束; 不銹鋼					
-	-	50,5	-	-	245-0025-8914
-	-	64,0	-	-	245-0050-8914
-	-	77,5	-	-	245-0055-8914



禾欣自動化企業社

HoShin Automation Co.,

TEL:06-3559720

FAX:06-3559725

<http://www.auto-matic.com.tw/index.html>


CONNECT TRI-CLAMP FITTING 245



額定尺寸	額定寬度管	法蘭盤外徑	重量	適合的軟管內徑 d2	訂購代碼
mm		法蘭	千克/個		
-	-	91,0	-	-	245-0065-8914
-	-	106,0	-	-	245-0080-8914
-	-	119,0	-	-	245-0100-8914
相配的附件; 接頭 DIN 32676用於焊接					
25	-	50,5	-	ø 25	245-0025-8913
32	-	50,5	-	ø 32	245-0032-8913
40	-	50,5	-	ø 40	245-0040-8913
50	-	64,0	-	ø 50	245-0050-8913
65	-	91,0	-	ø 65	245-0065-8913
80	-	106,0	-	ø 80	245-0080-8913
100	-	119,0	-	ø 100	245-0100-8913
相配的附件; 接頭 ISO 2852用於焊接					
-	1"	50,5	-	ø 25	245-0025-8917
-	1 1/2"	50,5	-	ø 40	245-0040-8917
-	2"	64,0	-	ø 50	245-0050-8917
-	2 1/2"	77,5	-	ø 65	245-0065-8917
-	3"	91,0	-	ø 75	245-0075-8917
-	4"	119,0	-	ø 100	245-0100-8917

所有指定的數值都是近似值，數字均在20°C攝氏度下取得，會根據實際使用環境情況而變化。請參閱技術附錄; 可提供其它長度及直徑產品

附件



CONNECT SAFETY
CLAMP ASSEMBLY
231



CONNECT PRESS
ASSEMBLY 232



CONNECT MOULD
ASSEMBLY 233



禾欣自動化企業社
HoShin Automation Co.,
TEL:06-3559720
FAX:06-3559725
<http://www.auto-matic.com.tw/index.html>